

Product Tech Sheet

SPECIFICATIONS

Model	Frequency Response	Signal-to-Noise Ratio	THD	Channel Separation	Input Range	DC Range	Fuse Rating
D3 400.2	20 - 20k Hz	100 dB	0.05%	75 dB (min.)	250 mV - 2.5 V (HL 0.5 - 5 V)	10.8 - 15.6 V	40 A
D3 400.4	20 - 20k Hz	100 dB	0.05%	75 dB (min.)	250 mV - 2.5 V (HL 0.5 - 5 V)	10.8 - 15.6 V	40 A
D3 600.1	20 - 250 Hz	90 dB	0.1%	n/a	250 mV - 3 V	11.5 - 14.4 V	70 A

RMS POWER

Model	4 Ohm Stereo	2 Ohm Stereo	4 Ohm Mono	2 Ohm Mono	1 Ohm Mono
D3 400.2	100 x 2	200 x 2	400 x 1	n/a	n/a
D3 400.4	50 x 4	100 x 4	200 x 2	n/a	n/a
D3 600.1	n/a	n/a	300 x 1	450 x 1	600 x 1

PHYSICAL DIMENSIONS

Model	(A) Length	(B) Width	(C) Height	Weight
D3 400.2	13.5"	8.5"	2.25"	9 lbs
D3 400.4	14.5"	8.5"	2.25"	10 lbs
D3 600.1	17"	8.5"	2.25"	13 lbs

