

TORQUE SPECIFICATION

Part Tightened	N·m	kgf·cm	ft·lbf	
Wheel nut	103	1,050	76	
Brake line union nut	15	155	11	
Brake booster clevis lock nut	26	260	20	
Brake pedal support assy x Body	16	160	12	
Brake pedal bracket No.3 x brake pedal support reinforcement	19	194	14	
Brake pedal x brake pedal support assy	34	350	25	
Brake booster assy x Body	16	160	12	
Brake master cylinder (3rd chamber) bleeder plug	11	112	8	
Brake master cylinder sub-assy x master cylinder (3rd chamber)	25	255	18	
Brake tube clamp x body	5.4	55	48 in.·lbf	
Front disc brake bleeder plug	8.3	85	74 in.·lbf	
Front brake cylinder mounting x Steering knuckle	107	1,090	79	
Front disc brake cylinder x Front disc brake cylinder mounting	34	350	25	
Front disc brake caliper x Flexible hose	29	296	21	
Rear disc brake bleeder plug	8.3	85	74 in.·lbf	
Rear disc brake cylinder mounting x Steering knuckle	88	900	65	
Rear disc brake cylinder x Rear disc brake cylinder mounting	34	35	25	
Rear disc brake caliper x Flexible hose	23	235	17	
Rear drum brake bleeder plug	11	112	8	
Rear wheel cylinder assyl x Baking plate	10	102	7	
Brake actuator x Brake actuator bracket 	w/ ABS:	5.4	55	48 in.·lbf
	w/ VSC:	5.4	55	48 in.·lbf
Brake actuator bracket x Body	20	199	14	
Front speed sensor wire harness clamp x shock absorber	19	192	14	
Front speed sensor x Steering knuckle	8.0	82	71 in.·lbf	
Rear speed sensor wire harness clamp x Body	8.0	82	71 in.·lbf	
Rear speed sensor wire harness clamp x Rear axle	8.0	82	71 in.·lbf	
Yawrate sensor bracket x Body	13	136	10	